



CB (XIAMEN) INDUSTRIAL CO.,LTD.  
B&T (ZHANGZHOU) CABLE CO., LTD

## UL 758 AWM Wire

### Single-conductor (PVC)

UL-1007	UL-1011	UL-1013	UL-1015	UL-1017	UL-1019	UL-1020	UL-1021	UL-1022	UL-1023
UL-1024	UL-1026	UL-1027	UL-1028	UL-1032	UL-1095	UL-1185	UL-1283	UL-1347	UL-1497
UL-1509	UL-1568	UL-1569	UL-1571	UL-1581	UL-1605	UL-1617	UL-1618	UL-1650	UL-1672
UL-1673	UL-1674	UL-1685	UL-1692	UL-1743	UL-1803	UL-1953	UL-10070		

### Single-conductor (SRPVC)

UL-10071	UL-10154	UL-10535	UL-1061	UL-11014	UL-1571				
----------	----------	----------	---------	----------	---------	--	--	--	--

### Multiple-conductor (PVC)

UL-2095	UL-2405	UL-2444	UL-2463	UL-2464	UL-2468	UL-2474	UL-2517	UL-2562	UL-2569
UL-2570	UL-2586	UL-2651	UL-2661	UL-2725	UL-2726	UL-2733	UL-2835	UL-2845	UL-2851
UL-2854	UL-2877	UL-2919	UL-2990	UL-20127	UL-20207	UL-20276	UL-20288	UL-20379	UL-20080

### Single-conductor (XLPVC)

UL-1429	UL-1430	UL-1431	UL-3314	UL-3315	UL-3317	UL-3443	UL-3454		
---------	---------	---------	---------	---------	---------	---------	---------	--	--

### Single-conductor (XLPE)

UL-3173	UL-3265	UL-3266	UL-3271	UL-3289	UL-3302	UL-3321	UL-3385	UL-3386	UL-3398
UL-10368									

### Single-conductor (FEP)

UL-1330	UL-1331	UL-1332	UL-1333	UL-1901	UL-1887	UL-1592	UL-10588		
---------	---------	---------	---------	---------	---------	---------	----------	--	--

### Single-conductor (PFA)

UL-10362	UL-1709	UL-1710	UL-1726	UL-1727					
----------	---------	---------	---------	---------	--	--	--	--	--

## UL62 Power Cord (PVC)

SVT	SJT	ST							
-----	-----	----	--	--	--	--	--	--	--

## VDE Flexible Cable

### Multiple-conductor (PVC)

H03VV-F 2x0.5mm2	H03VV-F 2x0.75mm2
H03VV-F 3x0.5mm2	H03VV-F 3x0.75mm2
H03VVH2-F 2x0.5mm2	H03VVH2-F 2x0.75mm2
H05VV-F 2x0.75mm2	H05VV-F 2x1.0mm2
H05VV-F 2x1.5mm2	H05VV-F 3x0.75mm2
H05VV-F 3x1.0mm2	H05VV-F 3x1.5mm2
H05VVH2-F 2x0.75mm2	H05VVH2-F 2x1.0mm2

## PSE Standard Power Cord

Solid Conductors: VVF (2-4 Cores) ×1.0MM	Stranded Conductors: VVF (2-4 Cores) ×2.0MM2
Solid Conductors: VVF (2-4 Cores) ×1.2MM	Stranded Conductors: VVF (2-4 Cores) ×3.5MM2
Solid Conductors: VVF (2-4 Cores) ×1.6MM	Stranded Conductors: VVF (2-4 Cores) ×5.5MM2
Solid Conductors: VVF (2-4 Cores) ×2.0MM	Stranded Conductors: VVF (2-4 Cores) ×8.0MM2
Solid Conductors: VVF (2-4 Cores) ×2.6MM	
Solid Conductors: VVF (2-4 Cores) ×3.2MM	

## Automotive Cable

### SAE American Standard Automotive Wire

GPT	TWP	SXL	GXL	TXL
-----	-----	-----	-----	-----

### ISO German Standard Automotive Wire

FLY	FLRY-A	FLRY-B	FLRYW-B	FLRX-B
-----	--------	--------	---------	--------

### JASO Japan Standard Automotive Wire

AV	AVS	AVSS	AVX	AEX
----	-----	------	-----	-----